

New!! PSB-AFOFB1388-AK

AF Open Front Paint Booth 13'W x 8'-6"H x 7'-6"D I.D.

The iDEAL 'A-Frame' Open Front Paint Booth is an economic, commercial grade open front paint booth designed to provide optimal 'air flow' with superior lighting for high-quality spray painting & finishing applications. The iDEAL Open Front Paint Booth is a great solution for industrial batch-type & automated production-type finishing systems. Air flows through the open front section of the booth, then passes through the work area towards the rear of booth into the filtered exhaust chamber. Filtered exhaust air is then drawn through the exhaust plenum & discharged upwards through the exhaust fan & ducting. Easily installed with heavy duty, precision punched 18 gauge panels allowing for quick nut & bolt assembly. Standard with bright white powder-coat finish, deluxe control panel, premium exhaust filters, hinged glass light fixtures & high-quality tube-axial exhaust fan to complete the package for a premium, highquality Open Front Paint Booth, all at a great value!

Exclusive Features!!


- ALWAYS IN STOCK, TYPICALLY SHIPS WITHIN 48 HOURS!
- DELUXE CONTROL PANEL INCLUDED
- DURABLE BRIGHT WHITE POWDER COAT FINISH

Standard Features

- HEAVY DUTY PRECISION PUNCHED 18 GAUGE PANELS
- OPTIMAL AIR FLOW W/ CFM 7,983 @ .5 STATIC PRESSURE
- UNIQUE 'A-FRAME' COMMERCIAL GRADE BOOTH DESIGN
- INSIDE OPENING DIMENSIONS: 13'W X 8'-6"H X 7'-6"D
- CONVENIENT 5/16" BOLT & NUT ASSEMBLY
- ALL ASSEMBLY HARDWARE, MANOMETER & SEALANT INCLUDED
- UL LISTED 24" DAYTON TUBE-AXIAL EXHAUST FAN W/ SPARK RESISTANT FAN BLADES
- NEMA RATED 2HP-3 PH 230/460VAC-60HZ MOTOR STANDARD
- PREMIUM AFC EXHAUST FILTERS
- SUPERIOR LIGHTING WITH (2EA) LDPI INDUSTRIAL LIGHT FIXTURES W/ INSIDE ACCESS HINGED GLASS DOOR
- TRUE 'DAYLIGHT COLOR' W/ GE T8 48" FLORESCENT LAMPS 32W 5000K, 4 LAMP
- MEETS AND/OR EXCEEDS ALL APPLICABLE OSHA & NFPA 33 REGULATIONS
- EASY TO INSTALL, OPERATE & MAINTAIN

Specifications

Paint Booth Model	PSB-AFOFB1388-AK
Inside Dimensions	13'W X 8-6"H X 7'-6"D
Outside Dimensions	13'-4"W X 8'-10"H X 10'-2"D
Fan / Motor	(1ea) - 24" Tube Axial Fan 2HP-3PH-230/460VAC-60HZ Non-Spark, NEMA Rated
CFM	7,983 @ .5 Static Pressure
Light Fixtures	(2ea) 48" 32W, T8 / 4 Bulb Light Fixtures UL & ETL Listed Cls1, Div2 - Groups A, B, C & D
Lamps	(8ea) T8 Florescent, 32W, 5000K - 48"L
Options	1 Phase Electrical Configuration
	8' Exhaust Duct Kit (25" Diameter)
	LED Lighting Upgrade Kit



DEAL

Premium Products at Affordable Prices!!

